

Vertical balers

B-series B3



WHERE SPACE IS LIMITED

The model B3 is the right choice of baler when you want to combine high compaction with a small footprint and low height. It fits where you need it.

An automatic full light indicator flashes when a bale is ready and prevents from overloading the chamber. You can easily remove the finished bale with the trolley included.

All steps of operation are made simple and safe, from the start of filling waste to tying of and removing the compacted bale.



Technical specifications

Press force (t)	3
Power supply	1x230V 50Hz 10A
Motor (kW)	1.1
Noise level (dB)	65-68
Cycle time (sec)	24
Dimensions WxDxH (mm)	940 x 715 x 1885
Weight (kg)	290
Filling opening WxH (mm)	770 x 460
Filling height (mm)	640
Chamber height (mm)	1000
Stroke (mm)	550
Bale size WxDxH (mm)	770 x 500 x 600
Bale weight cardboard (kg)	30-50
Bale weight plastic (kg)	40-60



1 Compact your waste and achieve high volume reduction. **2** Use the supplied trolley to remove the finished bale. **3** A spindle lock makes it safe and easy to open the lower door. **4** You replace strap rolls in front of the baler.

Safe operation

This baler complies with EU Safety Standard EN16500.

Easy to connect

Operates on single phase power supply.

Compact design

The B3 has a small footprint and low height.