

Vertical balers

X-series X25 Galv



FOR DEMANDING OR WET ENVIRONMENT

Bramidan has developed a range of galvanized balers especially designed for wet or demanding environments.

Model X25 Galv is very suitable for applications where there are no special hygienic requirements for stainless material, but where demands on surface treatment are so severe that an ordinary painted baler would have a very short lifetime.

Can also be placed outside - our unique range of X-series galvanized balers are also designed to withstand anything the weather throws at them. Hot-dip galvanized according to DS/EN 1461:2009.



Technical specifications

Press force (t)	25
Power supply	3x400V 50Hz 16A
Motor (kW)	4.0
Noise level (dB)	59-60
Cycle time (sec)	23
Dimensions WxDxH (mm)	1745 x 1260 x 1995
Weight (kg)	1410
Filling opening WxH (mm)	1090 x 530
Filling height (mm)	950
Chamber height (mm)	1380
Stroke (mm)	950
Bale size WxDxH (mm)	1200 x 800 x 800
Bale weight cardboard (kg)	200-300
Bale weight plastic (kg)	250-350



1 Compact your waste and eject the finished bale. **2** Remove and store the bale until collection. **3** The bale is ejected by a safe two-hand operation. **4** The cross cylinders ensure stable compression and a low overall height.

- **Easy installation**
Very low overall height
- **Safe and steady opening of door**
Operated by a strong threaded spindle
- **Noiseless**
Due to a unique hydraulic system

BRAMIDAN[®]
www.bramidan.com

Gama Engineering Ltd
16 Manachem Begin St.
Ramat Gan 52 700
Tel. +972 3 6130 666
Fax +972 3 6130 675
gama@actcom.co.il
www.gamaengineering.co.il



Scan the code and see a video of our X-series